



## Toothed Plate Connector DIN 1052

### C 10 double-sided and C 11 single-sided



#### C 10 double-sided

ø approx. mm	50	65	80	95	115
packing unit	50	50	25	25	25
weight approx. kg/100 pcs	4,440	8,250	10,520	13,400	17,600

#### C 11 one-sided

ø approx. mm	50	65	80	95	115
packing unit	50	50	25	25	25
weight approx. kg/100 pcs	4,600	8,400	13,000	15,500	21,500
for bolts	M 12	M 16	M 20	M 24	M 24

- Spikes completely formed out as per DIN 1052, which is only made possible due to production with natural sand in our foundry
- Final check for cracks or missing spikes during bundling
- High precision of the inner bore simplifying work and saving time, during installation
- Certificate 2.1 as per DIN EN ISO 10204:2004 upon request
- Made in Germany and consequently declared as **preferential original goods** as per directive 3351/83 EU

**MATERIAL:** Malleable cast iron EN-GJMB-350-10 acc. to DIN EN 1562  
**SURFACE:** Self colour, zinc plated acc. to DIN EN ISO 4042, hot dip galvanised, other surfaces on request  
**DIMENSIONS:** The above mentioned dimensions are indicate only. They correspond to the average allowed during the production process.

