




TOOTHED PLATE CONNECTOR EN 912 (DIN 1052)

TYPE C 11 SINGLE-SIDED AND C 10 DOUBLE-SIDED



C 11 single-sided

Diameter approx. mm	50	65	80	95	115
Quantity per bundle	50	50	25	25	25
Weight approx. kg/100 pcs	4,600	8,400	13,000	15,500	21,500
for bolts	M 12	M 16	M 20	M 24	M 24

C 10 double-sided

Diameter approx. mm	50	65	80	95	115
Quantity per bundle	50	50	25	25	25
Weight approx. kg/100 pcs	4,440	8,250	10,520	13,400	17,600

- » Complete formation of the pin as per DIN 1052, only possible due to natural sand production
- » Final inspection for cracking and missing pins when bundling
- » Precise formation of the inner bore = savings of time and labour when fastening the plate dowel at the assembly site
- » With certificate of compliance 2.1 as per EN 10204 – where required
- » Made in Germany.
- » The CE declaration of performance is available for downloading on our website.

MATERIAL: Temperguss EN-GJMB-350-10 nach DIN EN 1562

SURFACE FINISH: Bright, galvanised as per DIN EN ISO 4042, hot-dip galvanised, further finishes on request

All of the dimensions stated above are approximate and may deviate both upwards and downwards.